

The logo for Wilbert Precast, Inc. features the word "Wilbert" in a large, elegant, cursive script. Below it, the words "PRECAST, INC." are written in a smaller, bold, sans-serif, all-caps font. The entire logo is enclosed within a blue oval border that has a slight 3D effect with a lighter blue highlight on the top edge.

DRAWN BY:
TH

12/18/2025

-#4 U-BARS @ 5" O.C.E.W.

12" LARGER THAN TANK DIMENSIONS
EACH WAY, MAX BURY DEPTH 3'-0"

1" X 1" CONSEAL
CS-102 BUTYL
MASTIC @ JOINT

11381#-

TANK CONSTRUCTION UTILIZES 6000 PSI
CONCRETE AND GRADE 60 REBAR

GALLON CALCS:

6'-3"W X 7'-6"L X 5'-0"H X 7.48 = 1753 GALLONS

6'-3"W X 3'-9"L X 5'-0"H X 7.48 = 877 GALLONS

RISERS:
PVC: Ø24" AND FIBER COVER (TO GRADE)
CONCRETE: Ø24" X 8" OR 12" (6" BELOW GRADE)

BEDDING:
4" PEA GRAVEL (NO WATER PRESENT)

EXCAVATION:
12" LARGER THAN TANK DIMENSIONS
EACH WAY, MAX BURY DEPTH 3'-0"

1" X 1" CONSEAL
CS-102 BUTYL
MASTIC @ JOINT

11381#-

TANK CONSTRUCTION UTILIZES 6000 PSI
CONCRETE AND GRADE 60 REBAR

GALLON CALCS:

6'-3"W X 7'-6"L X 5'-0"H X 7.48 = 1753 GALLONS

6'-3"W X 3'-9"L X 5'-0"H X 7.48 = 877 GALLONS

RISERS:
PVC: Ø24" AND FIBER COVER (TO GRADE)
CONCRETE: Ø24" X 8" OR 12" (6" BELOW GRADE)

BEDDING:
4" PEA GRAVEL (NO WATER PRESENT)

EXCAVATION:
12" LARGER THAN TANK DIMENSIONS
EACH WAY, MAX BURY DEPTH 3'-0"

-#4 U-BARS @ 5" O.C.E.W.

DRAWN BY:
TH

12/18/2025